

## DATA SHEET



### SIROCCO CONFETTI

#### FEATURES:

- Confetti blower machine reaching 15 m Blow any size of confetti.
- Sucks small confetti or snow paper from a box with the supplied hose. High control on the amount of confetti to blow Electric confetti machine.
- No need of CO2 Directional blades made in aluminium Waterproof engine IP-68 of 720W
- Stand base with adjustable angle Tripod accommodation allowing to rotate the machine 360° Includes extra grille to blow and elevate sky dancers Compact and handy.
- Powerfull turbine with interchangeable FX head system.
- Take advantage of its interchangeable head system and combine its 5 different FX heads to get amazing stage FX.
- High quality finishings.

#### APPLICATION AND CAUTION:

- SIROCCO machine provided with this head has been designed for the effect outlined. Any use other than the one outlined excludes Oh!FX from all liability and warranty.
- Disconnect the machine from the power supply before changing the head and/or rear grid.
- Never turn on the motor without having a head and the rear grid in position and their screws tightened.
- Do not wet or cover the power supply. To clean it, use a damp cloth and dry it immediately.
- Use only consumables which are intended for this use and duly certified.
- In case of malfunction, do not attempt to disassemble the machine and contact your dealer. Any unauthorized alteration will invalidate the warranty.
- Only an adult and qualified person can operate the machine.

#### TECHNICAL SPECIFICATIONS:

**REF:** SIR-CONF/M

**SIZE \*motor in horizontal position:** 102 x 56 x 69cm

**MACHINE AND HEAD WEIGHT:** 31,20 Kg

**HEAD WEIGHT:** 5,50 Kg

**POWER SUPPLY WEIGHT:** 3,90 Kg

**VOLTAGE IN:** 100-240V. 50-60 Hz

**WORKING VOLTAGE:** 30V. DC

**NOMINAL POWER:** 720W

**PROTECTION:** IP-68 (not applicable to the power supply)

**WORKING TEMPERATURE:** -40/+110 °C

**MOTOR ROTATION SPEED:** 1200-4750 RPM

**NOISE LEVEL:** 85,6 dBa A 1m

**TIME FROM 0 RPM TO MAX SPEED:** 10s

**RANGE:** 0-15 m.

