

DATA SHEET

SIROCCO SNOW

FEATURES:



- Snow machine covering a distance of 15 m.
- Adjustable snow amount by regulating the pump.
- 2 sizes of snow flakes.
- Covers a wide area thanks to its rotating system.
- Powerful turbine with interchangeable FX head system.
- Take advantage of its interchangeable head system and combine its 5 different FX heads to get amazing stage FX.
- Directional blades made in aluminium.
- Waterproof engine IP-68 of 720W.
- Stand base with adjustable angle.
- Tripod accomodation allowing to rotate the machine 360°.
- Includes extra grille to blow and elevate sky dancers.
- Compact and handy.
- High quality finishings.

APPLICATION AND CAUTION:

- The SIROCCO snow pump is very sensitive to electrical current disturbances. Make sure that the power supply is completely stable and that the voltage and frequency are correct.
- Do not connect the SIROCCO snow pump to a power generator or power unit that does not have a current stabiliser. The pump could get damaged.
- Reattach it after cleaning.
- SIROCCO machine provided with this head has been designed for the effect outlined. Any use other than the one outlined excludes Oh!FX from all liability and warranty.
- Disconnect the machine from the power supply before changing the head and/or rear grid.
- Never turn on the motor without having a head and the rear grid in position and their screws tightened.
- Use only consumables which are intended for this use and duly certified.
- In case of malfunction, do not attempt to disassemble the machine and contact your dealer.

TECHNICAL SPECIFICATIONS:

REF : SIR-SNOW/M

SIZE *motor in horizontal position : 81 x 72 x 69 cm

MACHINE AND HEAD WEIGHT : 33,30 Kg

HEAD WEIGHT : 7,60 Kg

POWER SUPPLY WEIGHT : 3,90 Kg

VOLTAGE IN : 100-240V. 50-60 Hz

WORKING VOLTAGE : 30V. DC

NOMINAL POWER : 720W

PROTECTION : IP-68 (not aplicable to the power supply)

WORKING TEMPERATURES : 0/+50 °C

MOTOR ROTATION SPEED : 1200-4750 RPM

NOISE LEVEL : 85,6 dBa A 1m

TIME FROM 0 RPM TO MAX SPEED : 10s

MIN / MAX WATER PRESSURE : 43 / 87 PSI – 3 / 6 BAR

RANGE : 0-15 m.

PUMP POWER IN : 220V Version.

